

OSRAM Indoor Constant Current LED Drivers\_Linear 欧司朗室内恒流LED驱动电源\_长条形



Product Family 系列	Product Name 产品名称	EAN10 订货号	Dimming method 调光方式	Touch DIM 按键调光	SELV/ Non isolated 隔离/非隔离	Output Power 输出功率 [W]	Input Voltage 输入电压 [V]	Output Voltage 输出电压 [V]	Output Current 输出电流 [mA]	Max Efficiency 最大效率 [%]	Voltage Ripple 纹波电流 [%]	Power Factor 功率 因数	THD 总谐波 畸变率	Dimensions 外形尺寸 (LxWxH) [mm]	Ambient temperature range 工作环境温度 [°C]	Max Tc 最高温度 [°C]	Lifetime 产品寿命 [h]	IP Rating 防护等级	EL emergency lighting 防护等级	Safety Limiter Preload Case 适用灯具 防护等级	Cable clamp kit 压线夹	Programmer Tool 编程工具	Standard pack 标准包装 [pcs.]	Certificates & Approbations 认证	
Connected (Wireless)	OT WI 75/220-240/550 D NFC CA L	4062172267434	Casambi	No	Non-isolated	4-38	198-264	54...240	75...400	92	<1	≥0.95		280x30x21	-25...+60	75	100K	IP20	Yes	I	N/A	NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS*	
	OTI DX 35/220-240/400 D NFC L	4062172267458	Casambi	No	Non-isolated	6.5-75	198-264	54...240	125...550	93	<1	≥0.95		280x30x21	-25...+50	75	100K	IP20	Yes	I	N/A	NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS*	
	OTI DX 100/220-240/700 D NFC IND L	4062172267472	Casambi	No	Non-isolated	5.4-100	198-264	54...240	100...750	94	<1	≥0.95		280x30x21	-25...+50	75	100K	IP20	Yes	I	N/A	NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS*	
Connected (DALI)	OTI DEXAL -Non isolated D4I	OTI DX 35/220...240/400 D NFC L	4052899590380	DEXAL(D4I)	No	Non-isolated	4-38	220-240	54-240	75-400	90	<4	>0.95	<10	360x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DX 75/220...240/600 D NFC L	4052899590403	DEXAL(D4I)	No	Non-isolated	6.75-75	220-240	54-240	120-600	93	<4	>0.95	<10	360x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
	OTI DEXAL -Non isolated	OTI DX 100/220...240/700 D NFC IND L	4062172050883	DEXAL(D4I)	No	Non-isolated	23-100	220-240	64-300	200-700	up to 93	<1	>0.95	<10	425x30x21	-40...+70	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	No	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DX 150/220...240/650 D NFC IND L	4062172050920	DEXAL(D4I)	No	Non-isolated	43-150	220-240	64-300	250-850	90	<1	>0.95	<10	425x30x21	-40...+65	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	No	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
	OTI DALI-Non isolated LEDSET-2 Ultra Flat (11mm Height)	OTI DALI 35/220...240/400 D LT2 UF L	4052899957022	DALI	Yes	Non-isolated	4-38	220-240	54-240	75-400	93	<1	>0.98	<10	360x30x11	-20...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,KC,TIS
		OTI DALI 75/220...240/700 D LT2 UF L	4052899957046	DALI	Yes	Non-isolated	8-75	220-240	54-240	150-700	93	<1	>0.98	<10	360x30x11	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,KC,TIS
	OTI DALI - Non isolated NFC Tunable White (DT8)	OTI DALI 35/220...240/400 D NFC TW L	4052899990302	DALI	Yes	Non-isolated	4-38	220-240	45-240	75-400	90	<1	>0.95	<10	360x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 75/220...240/700 D NFC TW L	4052899990326	DALI	Yes	Non-isolated	8.1-75	220-240	50-240	125-700	91	<1	>0.95	<10	360x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
	OTI DALI - SELV NFC Tunable White(DT8)	OTI DALI 35/220-240/700 NFC TW L	4062172092982	DALI	Yes	SELV	4-38	220-240	15-54	200-700	90	<1	>0.95	<10	360x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 75/220-240/144 NFC TW L	4062172092968	DALI	Yes	SELV	8-75	220-240	15-54	400-1400	90	<1	>0.95	<10	360x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
	OTI DALI Industrial -Non isolated NFC	OTI DALI 75/220-240/550 D NFC IND L	4062172139670	DALI	Yes	Non-isolated	8-75	220-240	64-300	125-500	94	<1	>0.95	<10	360x30x21	-40...+70	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 100/220...240/700 D NFC IND L	4052899559516	DALI	Yes	Non-isolated	28-100	220-240	64-300	200-700	94	<1	>0.98	<8	360x30x21	-40...+60	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
	OTI DALI 150/220...240/140 D NFC IND L	4052899559530	DALI	Yes	Non-isolated	43-150	220-240	64-300	250-1000	95	<1	>0.98	<8	425x30x21	-40...+60	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
	OTI DALI 300/220...240/146 D NFC IND L	4062172186155	DALI	Yes	Non-isolated	80-300	220-240	60...300	250...1550	96	<1	>0.99	<8	360x45x28	-40...+65	85	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
OTI DALI - Non isolated NFC Flat (16mm Height)	OTI DALI 25/220-240/200 D NFC F L	4062172020749	DALI	Yes	Non-isolated	2.7-25	220-240	54-240	35-300	90.5	<1	>0.95	<9.5	280x30x16	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
	OTI DALI 35/220-240/400 D NFC F L	4062172020783	DALI	Yes	Non-isolated	4-38	220-240	54-240	75-400	92	<1	>0.97	<8	280x30x16	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
	OTI DALI 75/220-240/500 D NFC F L	4062172020787	DALI	Yes	Non-isolated	6-75	220-240	54-240	125-500	94	<1	>0.98	<5.5	280x30x16	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
OTI DALI- Non isolated LEDSET-2	OTI DALI 35/220...240/400 D LT2 L	4052899494220	DALI	Yes	Non-isolated	4-38	220-240	54-240	75-400	92	<1	>0.95	<10	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
		OTI DALI 60/220...240/550 D LT2 L	4052899494206	DALI	Yes	Non-isolated	6.4-60	220-240	54-240	120-550	93	<1	>0.95	<10	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 90/220...240/140 D LT2 L	4052899494268	DALI	Yes	Non-isolated	13.5-90	220-240	54-240	250-1000	94	<1	>0.95	<10	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
OTI DALI-Non isolated NFC	OTI DALI 90/220-240/700 D LT2 L	4052899494244	DALI	Yes	Non-isolated	13.5-90	220-240	54-240	250-700	93	<1	>0.95	<10	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
		OTI DALI 100/220...240/750 D NFC L	4062172125116	DALI	Yes	Non-isolated	5.4-100	220-240	54-260	100-750	94	<1	>0.95	<10	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
OTI DALI G2-SELV LEDSET-2	OTI DALI 35/220...240/700 LT2 L G2	4052899551783	DALI	Yes	SELV	4-37	220-240	15-54	200-700	90	<1	>0.95	<15	360x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
		OTI DALI 50/220...240/144 LT2 L G2	4052899551787	DALI	Yes	SELV	12-50	220-240	15-54	600-1400	91	<1	>0.95	<15	360x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 80/220...240/146 LT2 L	4052899028074	DALI	Yes	SELV	32-80	220-240	20-54	600-1550	90	<1	>0.95	<20	360x30x21	-25...+50	80	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 80/220...240/241 LT2 L	4052899028050	DALI	Yes	SELV	32-80	220-240	20-54	1000-2100	90	<1	>0.95	<20	360x30x21	-25...+45	80	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
OTI DALI-SELV NFC	OTI DALI 25/220-240/700 NFC L	4062172074940	DALI	Yes	SELV	2-28	220-240	15-54	180-700	90	<3	>0.95	<15	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
		OTI DALI 35/220-240/140 NFC L	4062172074964	DALI	Yes	SELV	4-37	220-240	15-54	200-1050	90	<3	>0.95	<15	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 50/220-240/144 NFC L	4062172074988	DALI	Yes	SELV	12-54	220-240	15-54	400-1400	91	<3	>0.95	<15	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic, NFC programmer	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		OTI DALI 80/220...240/241 NFC L	4062172238656	DALI	Yes	SELV	32.0-80	220-240	20-54	600-2100	91	<3	>0.95	<15	360x30x21	-25...+50	80	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP21	Yes	I	N/A	DALI Magic, NFC programmer	21	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
ETI DALI-SELV LEDSET-2	ETI DALI 25/220-240/500 LT2 L	4062172126212	DALI	N/A	SELV	3.6-25.5	220-240	20-51	180-500	86	<3	>0.95	<15	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS	
		ETI DALI 35/220-240/700 LT2 L	4062172126236	DALI	N/A	SELV	7-35.7	220-240	20-51	350-700	87	<3	>0.98	<15	280x30x21	-25...+50	80	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
		ETI DALI 75/220-240/144 LT2 L	4062172126250	DALI	N/A	SELV	12-71.4	220-240	20-51	600-1400	89	<3	>0.98	<15	280x30x21	-25...+50	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS
ETI DALI-Non isolated LEDSET-2	ETI DALI 25/220-240/300 D LT2 L	4062172053280	DALI	N/A	Non-isolated	3.0-25	220-240	54-240	35-300	90	<4	>0.95	<10	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS*	
		ETI DALI 35/220-240/400 D LT2 L	4062172053303	DALI	N/A	Non-isolated	4.0-38	220-240	54-240	75-400	92	<4	>0.95	<10	280x30x21	-25...+60	75	50K <sup>(1)</sup> /100K <sup>(2)</sup>	IP20	Yes	I	N/A	DALI Magic	20	CE,UKA,ENEC,CCC,RoM,EAC,BIS,KC,TIS*
		ETI DALI 75/220-240/500 D LT2 L	40621720																						



OSRAM Indoor Constant Current LED Drivers\_Linear 欧司朗室内恒流LED驱动电源\_长条形



Product Family, Product Name, EAN10, Dimming method, Touch DIM, SELV/ Non-isolated, Output Power, Input Voltage, Output Voltage, Output Current, Max Efficiency, Voltage, Power Factor, THD, Dimensions, Ambient temperature range, Max Tc, Lifetime, IP Rating, EL emergency lighting, Safety, Cable clamp kit, Programmer Tool, Standard pack, Certificates & Approbations.

备注: (1) 运行在最高Tc温度下的产品寿命, 最大失效率为10% (2) 运行的Tc温度比最高Tc温度低10°C下的产品寿命, 最大失效率为10% ★ 认证准备中 Remark: (1) At max. Tc temperature, max. failure rate of 10 % (2) Operating at 10 °C lower than max. Tc, max. failure rate of 10 % ★ In preparation



OSRAM Indoor Constant Current LED Drivers\_Linear 欧司朗室内恒流LED驱动电源\_长条形

